

### ARTICULATED BOOM LIFT

## XGA18ACK



The print does not belong to the contract, nor a part of the vehicle purchase contract. We reserve the right to revise the product model, paramenters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product.



# XGA18ACK Articulated boom lift



#### **FEATURES**

#### **MEASUREMENTS**

18m working height up to 256/350kg lift capacity

#### **PRODUCTIVITY**

1.83m x 0.76m working platform 256/350kg platform load capacity 160° platform rotation

4-wheel drive

2 steering wheels

30% theoretical gradeability

Horn

Solid rubber tires

Platform automatic leveling system

Fully proportional multi-function controls

Enable switch

Hourmeter record

Tilt alarm

Lift and lower alarm

Drive alarm

Lockable canopy

High/Slow speed mode


Flashing beacon

#### **POWER**

400Ah/48V Lead-acid batteries
1.9kW/12V DC emergency control unit
12V DC proportional control

#### **OPTIONS**

Axle balancing system
Turntable 360° continuous rotation
Platform working light
Tool tray
Non-marking tires
412Ah/51.2V Lithium batteries



Item	Unit	XGA18ACK
Working height	m	18
Platform height	m	16
Working radius	m	10.1
Lift capacity	kg	256/350
Occupant capacity	-	2
1st Boom luffing range	0	0~65
2nd Boom luffing range	0	-11~+75
Fly jib luffing range	0	-65~+70
Turntable rotation	0	355
Platform rotation	0	160
Drive Speed (retracted/extended)	km/h	4.8/0.6
Turning Radius (inside/outside)	m	3.2/4.7
Tailswing	mm	0
Ground clearance	mm	250
Gradeability	%	30
Tires	-	250-15/7.5
Control system	-	12V DC proportional control
Emergency control unit	kW∕V	1.9/12 DC
Batteries	V/Ah	48/400 Lead-acid (standard) 51.2/412 Lithium (optional)
Charger	V/A	48/35 Lead-acid (standard) 48/60 Lithium (optional)
Main power unit	kW∕V	12/32
Dirve Motor	kW∕V	3.3/32
Hydraulic tank	L	82
Weight	kg	8600
Platform size	mm	1830×760
a Length (transportation)	mm	7575/7550
b Width	mm	2320
c Height	mm	2350
d Wheelbase	mm	2360

SOLID TO SUCCEED